

Safety Data Sheet

Issue date 19-Jul-2021 Version 4

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHASE'S HOME VALUE HEAVY-DUTY ALL-PURPOSE CLEANER

Chemical name 7-7816-2

Other means of identification

Product code FG 419-0418-5

Synonyms General purpose cleaner

Recommended use of the chemical and restrictions on use
Recommended Use Various types of surfaces.
Uses advised against DO NOT USE ON FLOORS

Details of the supplier of the safety data sheet

Supplier Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-865-1000

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-865-1000

Emergency Telephone Number

 Company Phone Number
 708-865-1000

 24 Hour Emergency Phone Number
 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
FLAMMABLE AEROSOLS	Category 2
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

Warning

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray. Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear eye protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

Hazards not otherwise classified (HNOC)

Other Information

· Causes mild skin irritation

_

3. Composition/information on Ingredients

Common NameAll-purpose cleaner.SynonymsGeneral purpose cleaner.

Chemical Family MIXTURES. Formula 7-7816-2

Chemical nature Aqueous solution of organic solvent.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	90-95	*
2-Butoxyethanol	111-76-2	1-5	*
N-Butane	106-97-8	1-5	*
Diacetone alcohol	123-42-2	<1	*
Propane	74-98-6	<1	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contactWash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

Inhalation If overcome by vapor, move person to fresh air. Restore respiration if necessary. Get

medical attention if injury develops.

Ingestion Ingestion from an aerosol product is unlikely to occur.

Most important symptoms and effects, both acute and delayed

Symptoms Acute, Deliberate inhalation of concentrated vapor or mist may cause headaches.

Prolonged and repeated contact with the eyes may cause mild irritation. Chronic:

2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney

damage.

Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion productsThermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

AEROSOL STORAGE LEVEL I (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m ³	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³
		(vacated) TWA: 120 mg/m ³	
		(vacated) S*	
		S*	
N-Butane	STEL: 1000 ppm explosion	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8	hazard	(vacated) TWA: 1900 mg/m ³	TWA: 800 ppm
			TWA: 1900 mg/m ³
Diacetone alcohol	TWA: 50 ppm	TWA: 50 ppm	IDLH: 1800 ppm
123-42-2		TWA: 240 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 240 mg/m ³
		(vacated) TWA: 240 mg/m ³	
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion	TWA: 1800 mg/m ³	TWA: 1000 ppm
	hazard	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves, if desired.

Respiratory protection None required if used in a well-ventilated area.

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

ColorOdor thresholdNo information available

PropertyValuesRemarks • MethodpH10.2 +/- 0.5No information available

Melting point/freezing point

Boiling point/boiling range

Flash Point

No information available

product for which Flame Projection is 0

inches. Temperatures above 120 °F

may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available Flammability (solid, gas) No information available

Flammability Limits in Air

No information available

Upper flammability limitsNot availableLower Flammability LimitNot available

 Vapor pressure
 No information available

 Vapor Density
 No information available

 Polative Density
 No information available

Relative Density

0.99 +/-0.007 concentrate

No information available

Water solubility Soluble in water

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC content (%) 7.85

Density 8.24 - 8.31 lb/gal **Bulk Density** No information available

10. Stability and Reactivity

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information Primary routes of entry: Eye contact, skin contact, inhalation, ingestion (possible, but

consider unlikely).

Inhalation Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Eye Contact Can cause irritation after contact with eyes.

Skin contact May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

Ingestion This is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red

blood cell hemolysis and possible liver and kidney damage.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	-	-
7732-18-5			
2-Butoxyethanol	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
111-76-2			= 486 ppm (Rat) 4 h
N-Butane	-	-	= 658 g/m ³ (Rat) 4 h
106-97-8			
Diacetone alcohol	> 4 g/kg (Rat)	= 13630 mg/kg (Rabbit)	> 7.23 g/m³ (Rat) 8 h
123-42-2			
Propane	-	-	> 800000 ppm (Rat) 15 min
74-98-6			

Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

Serious eye damage/eye irritation

corrosivity Not applicable.
sensitization No a skin sensitizer.
Germ cell mutagenicity No information available.

Carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

Can cause irritation after contact with the eyes.

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3	Group 3		
111-76-2		,		

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 12113 mg/kg
ATEmix (dermal) 28351 mg/kg
ATEmix (inhalation-gas) 18017 mg/l
ATEmix (inhalation-dust/mist) 38.7 mg/l
ATEmix (inhalation-vapor) 8465 mg/l

12. Ecological Information

ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			Microorganisms	

2-Butoxyethanol	1490: 96 h Lepomis	1000: 48 h Daphnia magna
111-76-2	macrochirus mg/L LC50	mg/L EC50
	static	
	2950: 96 h Lepomis	
	macrochirus mg/L LC50	
Diacetone alcohol	420: 96 h Lepomis	
123-42-2	macrochirus mg/L LC50	
	420: 96 h Lepomis	
	macrochirus mg/L LC50	
	static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
2-Butoxyethanol	0.81
111-76-2	
N-Butane	2.89
106-97-8	
Diacetone alcohol	1.03
123-42-2	
Propane	2.3
74-98-6	

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity

Hazard Class NA

<u>IATA</u>

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

IMDG

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

All ingredients are listed or are excluded from listing on the DSL.

Legend:

DSL

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water			X
7732-18-5			
2-Butoxyethanol	X	X	X
111-76-2			
N-Butane	Χ	X	X
106-97-8			
Diacetone alcohol	X	X	X
123-42-2			
Propane	X	X	Х
74-98-6			

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
<u>NFPA</u>	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable
HMIS_	Health Hazards 1	Flammability 2	Physical hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 19-Jul-2021

Revision note

This SDS supersedes a previous SDS dated October 13, 2020.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet