



Issue date 25-Jul-2022

# Safety Data Sheet

Version 2

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

**Product name** CHAMPION SPRAYON PREMIUM SANDABLE ENAMEL PRIMER RED METAL PRIMER  
**Chemical name** 6-6399

### Other means of identification

**Product code** FG 419-0934-2  
**Synonyms** Spray Paint

### Recommended use of the chemical and restrictions on use

**Recommended Use** Interior/exterior enamel.  
**Uses advised against** Do not use on surfaces that come in contact with food

### Details of the supplier of the safety data sheet

Supplier Address	Manufacturer Address
Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-865-1000	Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-865-1000

### Emergency Telephone Number

**Company Phone Number** 708-865-1000  
**24 Hour Emergency Phone Number** 1-800-255-3924  
**Emergency telephone** ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

### Label Elements

#### EMERGENCY OVERVIEW

#### DANGER

#### **hazard statements**

Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
EXTREMELY FLAMMABLE AEROSOL  
Contains gas under pressure; may explode if heated



**Appearance** Dark red, viscous liquid

**Physical State** Aerosol

**Odor** Characteristic odor of paint.

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves, protective clothing, eye protection and face protection.  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing fumes, mist, vapors or spray.  
Use only outdoors or in a well-ventilated area  
Keep away from heat, sparks, open flames and hot surfaces. — No smoking  
Pressurized container: Do not pierce or burn, even after use  
Do not spray on an open flame or other ignition source

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor if you feel unwell  
IF SWALLOWED: Immediately call a POISON CENTER or doctor  
Do NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
Protect from sunlight

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

##### Other Information

- May be harmful in contact with skin
  - Causes mild skin irritation
  - Toxic to aquatic life with long lasting effects
  - Toxic to aquatic life
- 0% of this mixture consist of ingredient(s) of unknown toxicity.

### 3. Composition/information on Ingredients

**Synonyms** Spray Paint.  
**Chemical Family** MIXTURES.  
**Formula** 6-6399

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	35-40	*
Propane	74-98-6	15-20	*
N-Butane	106-97-8	10-15	*
Low Odor Mineral Spirits	64742-47-8	5-10	*
Cyclohexane	110-82-7	1-5	*

Magnesium Silicate	14807-96-6	1-5	*
Light Aliphatic Naphtha	64742-49-0	1-5	*
Solvent naphtha (petroleum), light aliphatic	64742-89-8	1-2	*
Red Iron Oxide	1309-37-1	1-5	*
Zinc Phosphate	7779-90-0	1-5	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. First aid measures

##### FIRST AID MEASURES

<b>Eye Contact</b>	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
<b>Skin contact</b>	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
<b>Inhalation</b>	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
<b>Ingestion</b>	Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.
-----------------	--

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard.
---------------------------	--

#### 5. Fire-fighting measures

##### Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

##### Explosion data

**Sensitivity to Mechanical Impact** Contents under pressure. This product is extremely flammable. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

**For emergency responders** Remove all sources of ignition.

### Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

## 7. Handling and Storage

### Precautions for safe handling

**Advice on safe handling** Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

**Incompatible Materials** Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

## 8. Exposure Controls/Personal Protection

### Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

N-Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Cyclohexane 110-82-7	TWA: 100 ppm	TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup> (vacated) TWA: 300 ppm (vacated) TWA: 1050 mg/m <sup>3</sup>	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>
Magnesium Silicate 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Red Iron Oxide 1309-37-1	TWA: 5 mg/m <sup>3</sup> respirable particulate matter	TWA: 10 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> fume and total dust Iron oxide (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction regulated under Rouge	IDLH: 2500 mg/m <sup>3</sup> Fe dust and fume TWA: 5 mg/m <sup>3</sup> Fe dust and fume

### Appropriate engineering controls

**Engineering controls** Use with adequate general or local exhaust ventilation.

### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Chemical resistant gloves required.

**Respiratory protection** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

**General hygiene considerations** Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

## **9. Physical and Chemical Properties**

### Information on basic physical and chemical properties

<b>Physical State</b>	Aerosol	<b>Odor</b>	Characteristic odor of paint.
<b>Appearance</b>	Dark red, viscous liquid	<b>Odor threshold</b>	No information available
<b>Color</b>	Dark red		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	Not applicable	Solvent-based product.	
<b>Melting point/freezing point</b>	Not applicable	No information available	
<b>Boiling point/boiling range</b>	Acetone 133 F/56.29 C	No information available	
<b>Flash Point</b>	Not available. This is an aerosol product with a Flame Projection of 18 in. with 3 in. flashback. Temperatures above 120 °F may cause cans to burst.	No information available	
<b>Evaporation Rate</b>	Faster than butyl acetate	No information available	
<b>Flammability (solid, gas)</b>		No information available	
<b>Flammability Limits in Air</b>		No information available	
<b>Upper flammability limits</b>	Not available		

Lower Flammability Limit	Not available	No information available
Vapor pressure		No information available
Vapor Density		No information available
Relative Density	0.865 concentrate	No information available
Water solubility	Insoluble in water	No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition Temperature		No information available
Decomposition temperature		No information available
Kinematic viscosity		No information available
Dynamic viscosity		No information available
Explosive properties	No information available	
Oxidizing properties	No information available	

#### Other Information

Softening point	No information available
Molecular weight	No information available
VOC content (%)	47.72%
Density	7.20 lb/gal concentrate
Bulk Density	No information available

## 10. Stability and Reactivity

#### Reactivity

Not applicable

#### Chemical stability

Stable.

#### Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

**hazardous polymerization** Hazardous polymerization does not occur.

#### Conditions to Avoid

Temperatures above 122 °F (50 °C).

#### Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

#### Hazardous decomposition products

Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

## 11. Toxicological Information

#### Information on likely routes of exposure

<b>Product Information</b>	This product has not been tested as whole. See below for information on ingredients.		
<b>Inhalation</b>	See data below.		
<b>Eye Contact</b>	Not data available.		
<b>Skin contact</b>	See data below.		
<b>Ingestion</b>	See data below.		

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h

**FG 419-0934-2 CHAMPION SPRAYON PREMIUM SANDABLE ENAMEL PRIMER RED METAL PRIMER**

Propane 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
N-Butane 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
Low Odor Mineral Spirits 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Cyclohexane 110-82-7	= 12705 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 9500 ppm ( Rat ) 4 h
Light Aliphatic Naphtha 64742-49-0	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 73680 ppm ( Rat ) 4 h
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
Red Iron Oxide 1309-37-1	> 10000 mg/kg ( Rat )	-	-
Zinc Phosphate 7779-90-0	> 5000 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** May cause skin irritation and reddening after prolonged or repeated contact with skin.  
**Serious eye damage/eye irritation** Irritating to eyes.  
**irritation** May cause skin and eye irritation.  
**corrosivity** Not applicable.  
**sensitization** No information available.  
**Germ cell mutagenicity** See Section 2 of this SDS.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Magnesium Silicate 14807-96-6		Group 2B Group 3		X
Red Iron Oxide 1309-37-1		Group 3		

**Reproductive toxicity** See Section 2 of this SDS.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** 0% of this mixture consist of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document**  
**ATEmix (oral)** 21118 mg/kg  
**ATEmix (dermal)** 31293 mg/kg  
**ATEmix (inhalation-gas)** 15680 mg/l  
**ATEmix (inhalation-dust/mist)** 15.9 mg/l  
**ATEmix (inhalation-vapor)** 840 mg/l

**12. Ecological Information**
**ecotoxicity**

See information listed below.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50

		LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50		Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Low Odor Mineral Spirits 64742-47-8		2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through		
Cyclohexane 110-82-7	500: 72 h Desmodemus subspicatus mg/L EC50	23.03 - 42.07: 96 h Pimephales promelas mg/L LC50 static 24.99 - 44.69: 96 h Lepomis macrochirus mg/L LC50 static 3.96 - 5.18: 96 h Pimephales promelas mg/L LC50 flow-through 48.87 - 68.76: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	
Magnesium Silicate 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		
Light Aliphatic Naphtha 64742-49-0		8.41: 96 h Oncorhynchus mykiss mg/L LC50 semi-static, closed		
Solvent naphtha (petroleum), light aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50			
Red Iron Oxide 1309-37-1		100000: 96 h Danio rerio mg/L LC50 static		

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
N-Butane 106-97-8	2.89
Cyclohexane 110-82-7	3.44

**Other adverse effects**

No information available

### 13. Disposal Considerations

**Waste treatment methods**
**Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002



**FG 419-0934-2 CHAMPION SPRAYON PREMIUM SANDABLE ENAMEL PRIMER RED METAL PRIMER**

67-64-1		F039		
Cyclohexane 110-82-7				U056

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Cyclohexane 110-82-7	Toxic Ignitable
Zinc Phosphate 7779-90-0	Toxic

**14. Transport Information****DOT**

UN/ID no	Limited Quantity
Proper Shipping Name	Consumer Commodity
Hazard Class	NA

**IATA**

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

**IMDG**

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
Marine pollutant	This product contains chemicals that are listed as marine pollutants.

**15. Regulatory information****International Inventories**

**TSCA** All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**DSL** All ingredients are listed or are excluded from listing on the DSL.

**Legend:**

TSCA - *United States Toxic Substances Control Act Section 8(b) Inventory*  
DSL/NDL - *Canadian Domestic Substances List/Non-Domestic Substances List*

**US Federal Regulations****SARA 313**

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Cyclohexane - 110-82-7	110-82-7	1-5	1.0
Zinc Phosphate - 7779-90-0	7779-90-0	1-5	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	yes
Chronic Health Hazard	yes

# FG 419-0934-2 CHAMPION SPRAYON PREMIUM SANDABLE ENAMEL PRIMER RED METAL PRIMER

Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

## CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cyclohexane 110-82-7	1000 lb			X
Zinc Phosphate 7779-90-0		X		

## CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Cyclohexane 110-82-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

## US State Regulations

### California Proposition 65

This product contains the following Proposition 65 chemicals. This product contains <0.1% ethyl benzene and <0.1% naphthalene, chemicals known to the State of California to cause cancer.

## U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Propane 74-98-6	X	X	X
N-Butane 106-97-8	X	X	X
Cyclohexane 110-82-7	X	X	X
Magnesium Silicate 14807-96-6	X	X	X
Red Iron Oxide 1309-37-1	X	X	X
Zinc Phosphate 7779-90-0	X		X

## U.S. EPA Label information

EPA Pesticide registration number Not applicable

## 16. Other information

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 1	<b>Physical and chemical properties</b> Not applicable
<b>HMIS</b>	<b>Health Hazards</b> 2*	<b>Flammability</b> 4	<b>Physical hazards</b> 1	<b>Personal Protection</b> B - Eyes and hands protection

Prepared by  
Issue date

Regulatory Department  
25-Jul-2022

**Revision note**

This SDS supersedes a previous SDS dated: 12-Feb-2018

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**