



Issue date 06-Mar-2018

Safety Data Sheet

Version 2

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED
Chemical name 6-6206

Other means of identification

Product code FG 419-4857-4
Synonyms Spray Paint

Recommended use of the chemical and restrictions on use

Recommended Use Field and pavement marking and striping paints.
Uses advised against Do not use on surfaces that are wet, cover with dust, dirt, grease, wax or loose paint.

Details of the supplier of the safety data sheet

| | |
|---|---|
| Supplier Address Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-273-1121 | Manufacturer Address Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-273-1121 |
|---|---|

Emergency Telephone Number

Company Phone Number 708-865-1000
24 Hour Emergency Phone Number 1-800-255-3924
Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

| | |
|--|---------------|
| Acute toxicity - Inhalation (Gases) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1B |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity | Category 1 |
| FLAMMABLE AEROSOLS | Category 1 |
| Gases Under Pressure | liquefied gas |

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
CAUSES SKIN IRRITATION
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
EXTREMELY FLAMMABLE AEROSOL
Contains gas under pressure; may explode if heated



Appearance Dark red, viscous liquid **Physical State** Aerosol **Odor** Characteristic odor of paint.

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves, protective clothing, eye protection and face protection.
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe fumes, mist, vapors or spray.
 Keep away from heat, sparks, open flames and hot surfaces. — No smoking
 Pressurized container: Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment: See additional cautionary statements on this label.
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 122 °F (50 °C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Harmful to aquatic life with long lasting effects
 - Harmful to aquatic life
- 0% of this mixture consist of ingredient(s) of unknown toxicity.

3. Composition/information on Ingredients

Synonyms Spray Paint.
Chemical Family MIXTURES.
Formula 6-6206

| Chemical name | CAS No | weight-% | Trade secret |
|-------------------|-----------|----------|--------------|
| Water | 7732-18-5 | 55-60 | * |
| Toluene | 108-88-3 | 10-15 | * |
| Propane | 74-98-6 | 5-10 | * |
| Calcium Carbonate | 471-34-1 | 5-10 | * |
| Acetone | 67-64-1 | 1-5 | * |
| N-Butane | 106-97-8 | 1-5 | * |
| Ethyl alcohol | 64-17-5 | 1-5 | * |

FG 419-4857-4 CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED

| | | | |
|-------------------------|------------|-----|---|
| Light Aliphatic Naphtha | 64742-49-0 | 1-5 | * |
|-------------------------|------------|-----|---|

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

| | |
|---------------------|---|
| Eye Contact | Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. |
| Skin contact | Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise. |
| Inhalation | If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise. |
| Ingestion | Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. |

Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Symptoms | Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|--|
| Note to physicians | Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard. |
|---------------------------|--|

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure. This product is extremely flammable. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

Incompatible Materials Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------------------|---|---|---|
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| Propane 74-98-6 | : See Appendix F: Minimal Oxygen Content | TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ | IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ |
| Calcium Carbonate 471-34-1 | - | - | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |
| Acetone 67-64-1 | STEL: 500 ppm TWA: 250 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |

FG 419-4857-4 CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED

| | | | |
|--------------------------|----------------|--|--|
| | | other sectors (vacated) STEL: 1000 ppm | |
| N-Butane 106-97-8 | STEL: 1000 ppm | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | TWA: 800 ppm TWA: 1900 mg/m ³ |
| Ethyl alcohol 64-17-5 | STEL: 1000 ppm | TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³ | IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³ |

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

- Eye/face Protection** Conventional eyeglasses to guard against splashing.
- Skin and Body Protection** Chemical resistant gloves required.
- Respiratory protection** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

| | | | |
|-------------------------------------|--|--------------------------|-------------------------------|
| Physical State | Aerosol | Odor | Characteristic odor of paint. |
| Appearance | Dark red, viscous liquid | Odor threshold | No information available |
| Color | APWA Red | | |
| Property | Values | Remarks • Method | |
| pH | Not applicable | Water-based mixture. | |
| Melting point/freezing point | Not applicable | No information available | |
| Boiling point/boiling range | Water 100 °C | No information available | |
| Flash Point | Not available. This is an aerosol product with a Flame Projection of 18 in. with 3 in. flashback. Temperatures above 120 °F may cause cans to burst. | No information available | |
| Evaporation Rate | Faster than butyl acetate | No information available | |
| Flammability (solid, gas) | | No information available | |
| Flammability Limits in Air | | No information available | |
| Upper flammability limits | Not available | | |
| Lower Flammability Limit | Not available | | |
| Vapor pressure | | No information available | |
| Vapor Density | | No information available | |
| Relative Density | 0.963 concentrate | No information available | |
| Water solubility | partially soluble | No information available | |
| Solubility in other solvents | | No information available | |
| Partition coefficient | | No information available | |
| Autoignition Temperature | | No information available | |
| Decomposition temperature | | No information available | |
| Kinematic viscosity | | No information available | |
| Dynamic viscosity | | No information available | |
| Explosive properties | No information available | | |

Oxidizing properties No information available

Other Information

Softening point No information available
Molecular weight No information available
VOC content (%) 29.05%
Density 8.02 lb/gal concentrate
Bulk Density No information available

10. Stability and Reactivity

Reactivity
 Not applicable No data available

Chemical stability
 Stable.

Possibility of hazardous reactions
 Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid
 Temperatures above 122 °F (50 °C).

Incompatible Materials
 Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

Hazardous decomposition products
 Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information This product has not been tested as whole. See below for information on ingredients.

Inhalation No data available.

Eye Contact No data available.

Skin contact No data available.

Ingestion No data available.

| Chemical name | Oral LD50 | dermal LD50 | Inhalation LC50 |
|---------------------------------------|----------------------|--------------------------|---------------------------------------|
| Water 7732-18-5 | > 90 mL/kg (Rat) | - | - |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| Propane 74-98-6 | - | - | = 658 mg/L (Rat) 4 h |
| Calcium Carbonate 471-34-1 | = 6450 mg/kg (Rat) | - | - |
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| N-Butane 106-97-8 | - | - | = 658 g/m ³ (Rat) 4 h |
| Ethyl alcohol 64-17-5 | = 7060 mg/kg (Rat) | - | = 124.7 mg/L (Rat) 4 h |
| Light Aliphatic Naphtha 64742-49-0 | > 5000 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 73680 ppm (Rat) 4 h |

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.
Serious eye damage/eye irritation Irritating to eyes.
irritation May cause skin and eye irritation.
corrosivity Not applicable.
sensitization No information available.
Germ cell mutagenicity See Section 2 of this SDS.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---------------------|-------|---------|-----|------|
| Toluene 108-88-3 | | Group 3 | | |

Reproductive toxicity See Section 2 of this SDS.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration Hazard No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0% of this mixture consist of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 21118 mg/kg
ATEmix (dermal) 31293 mg/kg
ATEmix (inhalation-gas) 15680 mg/l
ATEmix (inhalation-dust/mist) 15.9 mg/l
ATEmix (inhalation-vapor) 840 mg/l

12. Ecological Information

ecotoxicity

9.8% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name | Algae/aquatic plants | Fish | Toxicity to Microorganisms | Crustacea |
|---------------------|--|---|----------------------------|--|
| Toluene 108-88-3 | 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 12.6: 96 h Pimephales promelas mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static | EC50 = 19.7 mg/L 30 min | 11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static |
| Acetone 67-64-1 | | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L | EC50 = 14500 mg/L 15 min | 12600 - 12700: 48 h Daphnia magna mg/L EC50 |

FG 419-4857-4 CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED

| | | | | |
|---------------------------------------|--|--|---|---|
| | | LC50 8300: 96 h Lepomis macrochirus mg/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static | | 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static |
| Ethyl alcohol 64-17-5 | | 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static | EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min | 10800: 24 h Daphnia magna mg/L EC50 9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static |
| Light Aliphatic Naphtha 64742-49-0 | | | | 2.6: 96 h Chaetogammarus marinus mg/L LC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|--------------------------|-----------------------|
| Toluene 108-88-3 | 2.65 |
| Propane 74-98-6 | 2.3 |
| Acetone 67-64-1 | -0.24 |
| N-Butane 106-97-8 | 2.89 |
| Ethyl alcohol 64-17-5 | -0.32 |

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------------|------|---|------------------------|------------------------|
| Toluene 108-88-3 | U220 | Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151 | | U220 |
| Acetone 67-64-1 | | Included in waste stream: F039 | | U002 |

| Chemical name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|--|------------------------|
| Toluene 108-88-3 | | | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic | |

FG 419-4857-4 CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED

| | | | | |
|--|--|--|---|--|
| | | | hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | |
|--|--|--|---|--|

| Chemical name | California Hazardous Waste Status |
|--------------------------|-----------------------------------|
| Toluene 108-88-3 | Toxic Ignitable |
| Acetone 67-64-1 | Ignitable |
| Ethyl alcohol 64-17-5 | Toxic Ignitable |

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity
Hazard Class ORM-D

IATA

UN/ID no UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1

IMDG

UN/ID no UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Marine pollutant This product contains chemicals that are listed as marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

| Chemical name | CAS No | weight-% | SARA 313 - Threshold Values % |
|--------------------|----------|----------|-------------------------------|
| Toluene - 108-88-3 | 108-88-3 | 10-15 | 1.0 |

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard yes

FG 419-4857-4 CHAMPION SPRAYON INVERTED SPRAY PAINT APWA RED

Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Toluene 108-88-3 | 1000 lb | X | X | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------------|--------------------------|----------------|--|
| Toluene 108-88-3 | 1000 lb 1 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| Acetone 67-64-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals. This product contains <0.1% ethyl benzene, a chemical known to the State of California to cause cancer.

| Chemical name | California Proposition 65 |
|--------------------|---------------------------|
| Toluene - 108-88-3 | Developmental |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|--------------------------|------------|---------------|--------------|
| Water 7732-18-5 | | | X |
| Toluene 108-88-3 | X | X | X |
| Propane 74-98-6 | X | X | X |
| Acetone 67-64-1 | X | X | X |
| N-Butane 106-97-8 | X | X | X |
| Ethyl alcohol 64-17-5 | X | X | X |

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

| | | | | |
|-------------|--------------------------|-----------------------|---------------------------|--|
| NFPA | Health Hazards 2 | Flammability 4 | Instability 1 | Physical and chemical properties Not applicable Personal Protection B - Eyes and hands protection |
| HMIS | Health Hazards 2* | Flammability 4 | Physical hazards 1 | |

Prepared by Regulatory Department
Issue date 06-Mar-2018

Revision note

This SDS supersedes a previous SDS dated March 30, 2016.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet