



Issue date 20-May-2021

Safety Data Sheet

Version 3

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON PREMIUM ONE COAT ROOF ACCESSORIES PAINT
BIRCHWOOD
Chemical name 6-6195-2

Other means of identification

Product code FG 419-4876-2
Synonyms Spray Paint

Recommended use of the chemical and restrictions on use

Recommended Use Roof coating.
Uses advised against Do not use on surfaces that come in contact with food

Details of the supplier of the safety data sheet

Supplier Address	Manufacturer Address
Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-865-1000	Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-865-1000

Emergency Telephone Number

Company Phone Number 708-865-1000
24 Hour Emergency Phone Number 1-800-255-3924
Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
EXTREMELY FLAMMABLE AEROSOL
 Contains gas under pressure; may explode if heated



Appearance Light brown, viscous liquid **Physical State** Aerosol **Odor** Characteristic odor of paint.

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves, protective clothing, eye protection and face protection.
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe fumes, mist, vapors or spray.
 Keep away from heat, sparks, open flames and hot surfaces. — No smoking
 Pressurized container: Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment: See additional cautionary statements on this label.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Causes mild skin irritation
 - Harmful to aquatic life with long lasting effects
 - Harmful to aquatic life
- Less than 2 % of the mixture consists of ingredient(s) of unknown toxicity.

3. Composition/information on Ingredients

Synonyms Spray Paint.

Chemical Family MIXTURES.
Formula 6-6195-2

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	35-40	*
Propane	74-98-6	20-25	*
N-Butane	106-97-8	10-15	*
Magnesium Silicate	14807-96-6	5-10	*
Toluene	108-88-3	5-10	*
Light Aliphatic Naphtha	64742-49-0	1-5	*
Titanium Dioxide	13463-67-7	<1	*
Carbon BLACK	1333-86-4	<1	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
Skin contact	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
Inhalation	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
Ingestion	Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard.
---------------------------	--

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure. This product is extremely flammable. Keep away from heat,

Sensitivity to Static Discharge

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).
Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

For emergency responders

Remove all sources of ignition.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Methods for cleaning up

Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling

Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

		apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
N-Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³
Magnesium Silicate 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Carbon BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Chemical resistant gloves required.

Respiratory protection Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Characteristic odor of paint.
Appearance	Light brown, viscous liquid	Odor threshold	No information available
Color	Light brown		
Property	Values	Remarks • Method	
pH	Not applicable	Solvent-based product.	

Melting point/freezing point	Not applicable	No information available
Boiling point/boiling range	Acetone 133 F/56.29 C	No information available
Flash Point	Not available. This is an aerosol product with a Flame Projection of 18 in. with 3 in. flashback. Temperatures above 120 °F may cause cans to burst.	No information available
Evaporation Rate	Faster than butyl acetate	No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		No information available
Upper flammability limits	Not available	
Lower Flammability Limit	Not available	
Vapor pressure		No information available
Vapor Density		No information available
Relative Density	0.924 concentrate	No information available
Water solubility	Insoluble in water	No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition Temperature		No information available
Decomposition temperature		No information available
Kinematic viscosity		No information available
Dynamic viscosity		No information available
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC content (%)	46.2%
Density	7.69 lb/gal concentrate
Bulk Density	No information available

10. Stability and Reactivity

Reactivity

Not applicable No data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information	This product has not been tested as whole. See below for information on ingredients.
Inhalation	No data available.

Eye Contact No data available.

Skin contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
N-Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Light Aliphatic Naphtha 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Carbon BLACK 1333-86-4	> 15400 mg/kg (Rat)	-	> 4.6 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.
Serious eye damage/eye irritation Irritating to eyes.
irritation May cause skin and eye irritation.
corrosivity Not applicable.
sensitization No information available.
Germ cell mutagenicity See Section 2 of this SDS.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Magnesium Silicate 14807-96-6		Group 2B Group 3		X
Toluene 108-88-3		Group 3		
Titanium Dioxide 13463-67-7		Group 2B		X
Carbon BLACK 1333-86-4	A3	Group 2B		X

Reproductive toxicity See Section 2 of this SDS.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration Hazard No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity Less than 2 % of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document .
ATEmix (oral) 21118 mg/kg
ATEmix (dermal) 31293 mg/kg
ATEmix (inhalation-gas) 15680 mg/l
ATEmix (inhalation-dust/mist) 15.9 mg/l
ATEmix (inhalation-vapor) 840 mg/l

12. Ecological Information

ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Magnesium Silicate 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Light Aliphatic Naphtha 64742-49-0		8.41: 96 h Oncorhynchus mykiss mg/L LC50 semi-static, closed		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
N-Butane 106-97-8	2.89
Toluene 108-88-3	2.7

Other adverse effects

No information available

13. Disposal Considerations
Waste treatment methods

Disposal of wastes

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable

14. Transport Information
DOT

UN/ID no	Limited Quantity
Proper Shipping Name	Consumer Commodity
Hazard Class	ORM-D

IATA

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

IMDG

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
Marine pollutant	This product contains chemicals that are listed as marine pollutants.

15. Regulatory information**International Inventories****TSCA**

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

DSL

All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	5-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals. This product contains <0.1% ethyl benzene and <0.1% naphthalene, chemicals known to the State of California to cause cancer.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental
Titanium Dioxide - 13463-67-7	Carcinogen
Carbon BLACK - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone	X	X	X

67-64-1			
Propane 74-98-6	X	X	X
N-Butane 106-97-8	X	X	X
Magnesium Silicate 14807-96-6	X	X	X
Toluene 108-88-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Carbon BLACK 1333-86-4	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

NFPA	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2*	Flammability 4	Physical hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department
 Issue date 20-May-2021
 Revision note
 This SDS supersedes a previous SDS dated April 15, 2020.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet