

Safety Data Sheet

Issue date 10-Aug-2021 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name PROSALL OVEN TECH OVEN CLEANER

Chemical name 7-7603-1

Other means of identification

Product code FG 433-1107-5 Synonyms Oven and grill cleaner

Recommended use of the chemical and restrictions on use Recommended Use Stoves, ovens and grills.

Uses advised against DO NOT USE ON FLOORS Do not use on tile, plastic, leather, copper, painted and

varnished surfaces.

Details of the supplier of the safety data sheet

Supplier Address
ProsALL Products a Division of Chase
Products Co.
Products Co.
P.O. Box 7502
Westchester, IL 60154

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-865-1000

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 2A
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

Causes severe skin burns and eye damage

Causes serious eye irritation

Contains gas under pressure; may explode if heated



Appearance Yellowish, viscous liquid Physical State Aerosol Odor Strong, characteristic odor

Precautionary Statements - Prevention

Do not breathe fumes, mist, vapors or spray.

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary Statements - Response

Specific measures. See additional cautionary statements on this label.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor

IF SWALLOWED: rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life

-

3. Composition/information on Ingredients

Common NameOven and grill cleaner.SynonymsOven and grill cleaner.

Chemical Family MIXTURES. Formula 7-7603-1

Chemical nature Aqueous alkaline solution.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	80-85	*
Triethylene Glycol	112-27-6	1-5	*
N-Butane	106-97-8	1-5	*
Sodium hydroxide	1310-73-2	1-5	*
Potassium hydroxide	1310-58-3	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20

minutes. Call a poison control center or doctor for treatment advise.

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

Inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion Call a poison control center or doctor for treatment advice. Have person sip a glass of water

if able to swallow. Do not induce vomiting unless told to do so by a poison control center or

doctor. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Danger - contains sodium hydroxide. Injurious if sprayed on yes. Contact with eyes

may result on eye damage. Irritant to skin. Prolonged contact with skin may cause severe burns. Inhalation of vapor or mist may cause headaches, dizziness and nausea. Vapors

may irritate the upper-respiratory tract system.

Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsUse with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Avoid contact with skin. Avoid getting spray into eyes. Do not deliberately inhale vapor or

mist. Do not contaminate food or food handling surfaces. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

AEROSOL STORAGE LEVEL I (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers. Avoid contact with tile, plastic,

leather, copper, painted and varnished surfaces.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Butane	STEL: 1000 ppm explosion	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8	hazard	(vacated) TWA: 1900 mg/m ³	TWA: 800 ppm
			TWA: 1900 mg/m ³
Sodium hydroxide	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³	IDLH: 10 mg/m ³
1310-73-2		(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Potassium hydroxide	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
1310-58-3			
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion	TWA: 1800 mg/m ³	TWA: 1000 ppm
hazard		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Rubber, vinyl or household type gloves required.

fumes disipate.

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

AppearanceYellowish, viscous liquidOdorStrong, characteristic

odor

Color light yellow Odor threshold No information available

Property
pHValues
12.9 to 13.5Remarks • Method
No information availableMelting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeWater 212 °F/100 °CNo information available

Flash Point

Not applicable. This is an aerosol

Product for which Flame Projection is 0

No information available

in. with 0 in flashback. Product was tested for Enclosed Space Ignition Test and is not a flammable aerosol as defined on 29CFR 1910.122 Appendix

B.3.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableRelative Density1.056 concentrateNo information available

Water solubility Soluble in water

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information available

Dynamic viscosity

No information available

No information available

Explosive propertiesNo information available **Oxidizing properties**No information available

Other Information

Softening point No information available Molecular weight No information available

VOC content (%) 7.84% **Density** 8.80 lb/gal

Bulk Density No information available

10. Stability and Reactivity

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers. Avoid contact with tile, plastic, leather, copper, painted and varnished surfaces.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information Danger contains Sodium Hydroxide

Inhalation Vapors may irritate the upper-respiratory tract system. Inhalation of vapor or mist may

cause headaches, dizziness and nausea.

Eye Contact Injurious if sprayed on eyes. Contact with eyes may result on eye damage.

Danger, contains sodium hydroxide. Irritant to skin. Prolonged contact with skin may cause Skin contact

severe burns.

Ingestion This is an aerosol product, ingestion is unlikely to occur. MAY BE HARMFUL IF

SWALLOWED.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	-	-
7732-18-5			
Triethylene Glycol	= 17 g/kg(Rat)	> 20 mL/kg (Rabbit)	> 3.9 mg/L (Rat) 4 h
112-27-6			
N-Butane	-	-	= 658 g/m ³ (Rat) 4 h
106-97-8			
Sodium hydroxide	= 325 mg/kg (Rat)	= 1350 mg/kg (Rabbit)	-
1310-73-2			
Potassium hydroxide	= 284 mg/kg (Rat)	-	-
1310-58-3			
Propane	-	-	> 800000 ppm (Rat) 15 min
74-98-6			, ,

Information on toxicological effects

Symptoms Vapors may be irritating to eyes, nose, throat, and lungs.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause severe burns after prolonged contact with skin.

Serious eye damage/eye irritation

Risk of serious damage to eyes. Contains sodium hydroxide, can be corrosive to skin and eyes. corrosivity

sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive toxicity No information available. STOT - single exposure No information available. STOT - repeated exposure No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 17749 mg/kg 46056 mg/kg ATEmix (dermal) 8757000 mg/l ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) 46.1 mg/l ATEmix (inhalation-vapor) 14403 mg/l

12. Ecological Information

ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
------------------------------------	------	----------------------------	-----------

Triathulana Olugal	F0000 00700, 00 h	40.400; 40 h Danhaia asa asa
Triethylene Glycol	56200 - 63700: 96 h	42426: 48 h Daphnia magna
112-27-6	Pimephales promelas mg/L	mg/L EC50
	LC50 flow-through	
	10000: 96 h Lepomis	
	macrochirus mg/L LC50	
	static	
	61000: 96 h Lepomis	
	macrochirus mg/L LC50	
	flow-through	
Sodium hydroxide	45.4: 96 h Oncorhynchus	
1310-73-2	mykiss mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Triethylene Glycol 112-27-6	-1.98
N-Butane 106-97-8	2.89
Potassium hydroxide	0.65
1310-58-3	0.83
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	California Hazardous Waste Status	
Sodium hydroxide	Toxic	
1310-73-2	Corrosive	
Potassium hydroxide	Toxic	
1310-58-3	Corrosive	

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity

Hazard Class N

IATA

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable, containing substances in Class 8 packing group II

Hazard Class 2.1 (8)

IMDG

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 (8)

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000 lb			Х
Potassium hydroxide 1310-58-3	1000 lb			Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide	1000 lb		RQ 1000 lb final RQ
1310-73-2			RQ 454 kg final RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water			Χ

7732-18-5			
Triethylene Glycol 112-27-6			Х
N-Butane 106-97-8	X	X	X
Sodium hydroxide 1310-73-2	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
<u>NFPA</u>	Health Hazards 3	Flammability 1	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 3	Flammability 2	Physical hazards 1	Personal Protection B - Eyes and hands protection

Issue date 10-Aug-2021 Revision note

This SDS supersedes a previous MSDS dated August 25, 2005.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet
