



Issue date 10-Mar-2015

Safety Data Sheet

Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name PROSALL WINDEMERE WINDOW & MIRROR CLEANER
Chemical name 7-7694-1

Other means of identification

Product code FG 433-1110-6
Synonyms Glass Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use Glass surfaces.
Uses advised against DO NOT USE ON FLOORS

Details of the supplier of the safety data sheet

Supplier Address
ProsALL Products a Division of Chase
Products Co.
P.O. Box 7502
Westchester, IL 60154

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000
24 Hour Emergency Phone Number 1-800-255-3924
Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

Warning

hazard statements

HARMFUL IF INHALED
Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Foam Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Hazards not otherwise classified (HNOC)

Other Information

- Causes mild skin irritation

-

3. Composition/information on Ingredients

Common Name Glass Cleaner.
Synonyms Glass Cleaner.
Chemical Family MIXTURES.
Formula 7-7694-1
Chemical nature Aqueous solution of organic solvent.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	85-90	*
2-Butoxyethanol	111-76-2	1-5	*
N-Butane	106-97-8	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinogenes are listed when present at 0.1% or greater.

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

inhalation If overcome by vapor, move person to fresh air. Restore respiration if necessary. Get medical attention if injury develops.

INGESTION Ingestion from an aerosol product is unlikely to occur.

Most important symptoms and effects, both acute and delayed

Symptoms Acute, Deliberate inhalation of concentrated vapor or mist may cause headaches. Prolonged and repeated contact with the eyes may cause mild irritation. Chronic: 2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage.

Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children. **AEROSOL STORAGE LEVEL I (NFPA-30B) .**

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm

FG 433-1110-6 PROSALL WINDEMERE WINDOW & MIRROR CLEANER

111-76-2		TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	TWA: 5 ppm TWA: 24 mg/m ³
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m ³ (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m ³ (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m ³ (vacated) S* S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m ³ STEL: 30 ppm STEL: 105 mg/m ³

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves, if desired.

Respiratory protection None required if used in a well-ventilated area .

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

<p>Physical State Appearance Color</p>	<p>Foam Aerosol Clear liquid that will be aerosolized. clear</p>	<p>Odor Odor threshold</p>	<p>Perfumed. No information available</p>
<p>Property pH Melting point/freezing point Boiling point/boiling range Flash Point</p>	<p>Values 10.95 - 11.01 Not applicable Water 212 °F/100 °C Not applicable. This is an aerosol product for which Flame Projection is 0 in. with 0 in flashback. Product was tested for Enclosed Space Ignition Test and is not a flammable aerosol as defined on 29CFR 1910.122 Appendix B.3.</p>	<p>Remarks • Method No information available No information available No information available No information available</p>	
<p>Evaporation Rate Flammability (solid, gas) Flammability Limits in Air Upper flammability limits Lower Flammability Limit Vapor pressure Vapor Density Specific gravity Water solubility Solubility in other solvents Partition coefficient</p>	<p>Faster than butyl acetate Not available Not available</p>	<p>No information available No information available No information available</p>	
	<p>0.992 - 1.102 concentrate</p>	<p>No information available No information available Soluble in water No information available No information available</p>	

Autoignition Temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other Information

Softening point	No information available
Molecular weight	No information available
VOC content (%)	8.88%
Density	8.26 - 8.35 lb/gal
Bulk Density	No information available

10. Stability and Reactivity

Reactivity
 Not applicable
 Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information	Primary routes of entry: Eye contact, skin contact, inhalation, ingestion (possible, but consider unlikely).
inhalation	Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.
Eye Contact	Can cause irritation after contact with eyes.
Skin contact	May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.
INGESTION	This is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red blood cell hemolysis and possible liver and kidney damage.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.

Serious eye damage/eye irritation Can cause irritation after contact with the eyes.

corrosivity Not applicable.

sensitization No a skin sensitizer.

Germ Cell Mutagenicity No information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity -

The following values are calculated based on chapter 3.1 of the GHS document .

- ATEmix (oral) 9812 mg/kg
- ATEmix (dermal) 22965 mg/kg
- ATEmix (inhalation-gas) 14583 mg/l
- ATEmix (inhalation-dust/mist) 31.3 mg/l
- ATEmix (inhalation-vapor) 5821 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

4.96% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

14. Transport Information

DOT Limited quantity (LQ) Glass Cleaner
UN/ID no UN1950
Proper Shipping Name Limited quantity (LQ)
Hazard Class 2.1
Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40

FG 433-1110-6 PROSALL WINDEMERE WINDOW & MIRROR CLEANER

CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
2-Butoxyethanol 111-76-2	X	X	X
N-Butane 106-97-8	X	X	X
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

<u>NFPA</u>	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable Personal Protection B - Eyes and hands protection
<u>HMIS</u>	Health Hazards 1	Flammability 2	Physical Hazards 1	

Issue date 10-Mar-2015

Revision note

This SDS supersedes a previous SDS dated September 16, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet